

Data sheet

SPARK TACTICAL



GENERAL

Art. no.:	A-057
EAN:	4030281011026
Standard:	EN 12841-C:2006 EN 15151-1:2012 EN 341-2A:2011

E-class number:	40-02-01-06
Customs no.:	84798997

Data sheet

SPARK TACTICAL

SPARK TACTICAL is developed for permanent use under the toughest conditions. The product version developed especially for tactical operations combines the advantages of the best abseiling devices for industrial and rescue use. SPARK TACTICAL is characterised in particular by the conception without anti-panic-function, which enables fast, precise and uninterrupted abseiling.

Intuitive and simple rope handling, while the carabiner on the harness can remain connected to the device, the well thought-out ergonomics and the precise operation of the lever allow for the best handling. Thanks to the sophisticated rope guide inside the device, the rope is protected against twisting and kinking as well as heavy wear.

- Fast, precise, uninterrupted abseiling possible without anti-panic-function
- Outstanding handling thanks to compact, ergonomic design and intuitive rope guide
- Durable and robust: 100% metal without vulnerable plastic parts

GENERAL

Internat. standard:

FEATURES

Abseiling speed:	2,00 m/s
Max. service life:	30 Years
Max. number of persons:	1, 2 in rescue operations
Temperature:	from 60 °C to -30 °C

DIMENSIONS

Size:	47x79x175mm
Weight:	0,51 kg

MATERIAL

Material:	Aluminium, Steel
-----------	------------------

WORKING LOAD

EN 12841-C:2006	max. 250kg
EN 341-2A:2011	30kg - 200kg
ANSI Z359.1	59kg - 141kg